

Screwed connection Rp 1 x G 1½, 1 Set

Pipe installation

Article number: 4092741

Data sheet

Technical data

For Wilo pumps	Nominal diameter 25

Connection

Inlet connection	G 1½
Outlet connection	R 1
Pump connection	G 1½
Pipe connection	R 1

Dimensions

Dimensions *L1*	7 mm
Dimensions *l2*	9 mm

Materials

Material	EN-GJMW-400-5, yellow-coated
Material nut	EN-GJMW-400-5, yellow-coated

Ordering information

Length *L*	0 mm
Width *W*	160 mm
Height *H*	250 mm
Net weight, approx.	0.34 kg
Make	Wilo
Product description	Screwed connection Rp 1 x G 1½, 1 Set
Item no.	4092741

Tender text

Screwed connections for circulation pumps with threaded connection.

Malleable cast iron screwed connections, inserts with female threads for connection to steel pipes (DIN 2440) with Whitworth pipe threads according to DIN 10226-1.

Scope of delivery

- 1 set of malleable cast iron screwed connections consisting of:
- 2 union nuts
- 2 inserts
- 2 flat gaskets

Technical data

Inlet connection	G 1½
Outlet connection	R 1
Max. fluid temperature	110 °C
Material	EN-GJMW-400-5, yellow-coated

Technical data

Quantity per order unit	1 set
Net weight, approx.	0.34 kg
Make	Wilo
Item no.	4092741